



600 Guy Paine Road

Macon, Ga

31206

USA

Tel. (478) 781.9488

## SD POLYMERS SPUNBOND POLYESTER TYPE 140 REINFORCED

### Product Description

SD SD Polymers Spunbond Polyester Type 140 Reinforced is a continuous filament polyester with glass reinforcement.

### Technical Information

Physical Properties	Standard Values
Mat Weight, g/m <sup>2</sup>	140 (min 135)
Thickness, mm	0.25 (min 0.2)
Shrinkage @ 200°C, % MD	-0.6 (min -0.25)

Mechanical Properties	Standard Values
Strip Tensile Strength at break, lbs/in. MD	48 (min 35)
Strip Tensile Strength at break, lbs/in. CD	28 (min 25)
Strip Elongation at break, % MD	28 (min 25)
Strip Elongation at break, % CD	40 (min 35)

## Product Data Sheet

NOTICE: ALL STATEMENTS, INFORMATION AND DATA GIVEN HEREIN ARE RELIABLE BUT ARE PRESENTED WITHOUT GUARANTY, WARRANTY, OR RESPONSIBILITY OF ANY KIND, EXPRESSED OR IMPLIED. STATEMENTS OR SUGGESTIONS CONCERNING POSSIBLE USE OF OUR PRODUCTS ARE MADE WITHOUT REPRESENTATION OR WARRANTY THAT ANY SUCH USE IS FREE OR PATENT INFRINGEMENT, AND ARE NOT RECOMMENDATIONS TO INFRINGE ANY PATENT. THE USER SHOULD NOT ASSUME THAT ALL SAFETY MEASURES ARE INDICATED, OR THAT OTHER MEASURES MAY NOT BE REQUIRED.